

## HMT200A

- Hot melt adhesive tape
- Designed for use with heat-shrink sleeves and mouldings
- The tape flows when heated and provides permanent air and water tight seals
- Supplied in 50m reels.

Hot Melt Adhesive Tape (HMT200A)	
Min. Working Temperature	<b>-55°C</b>
Max. Working Temperature	<b>105°C</b>
Softening Point	<b>110°C</b>
Peel Strength Halogen Content	<b>XLPE/Metal 100N / 25mm XLPE/XLPE 210N / 25mm PVC/PVC 80N / 25mm</b>
Relevant Standards	<b>Free</b>
Standard Colours	<b>Def Stan 59-97 Type W (w) Golden Brown</b>

All dimensions are in mm (nominal) and are subject to technical modification.



## IL

- Polythene melttable liner for use with heatshrinkable sleeves
- The liner melts and flows to provide an effective environmental seal with the substrate

Melttable Inner Liner (IL)			
Min. Working Temperature		<b>-60°C</b>	
Max. Working Temperature		<b>135°C</b>	
Softening Point		<b>130°C</b>	
Halogen Content		<b>Halogen Free</b>	
Standard Colours		<b>Translucent</b>	
Size	Inside Diameter	Wall Thickness	Heatshrink Size Reference
<b>22</b>	2.2	0.38	32
<b>37</b>	3.7	0.38	48
<b>53</b>	5.3	0.38	64
<b>85</b>	8.5	0.38	95
<b>117</b>	11.7	0.38	127

All dimensions are in mm (nominal) and are subject to technical modification.

